

Pvc Kaplı Örgülü Bakır İletkenler

Pvc Covered Stranded Copper Cable



Ürün Kodu	Malzeme	Kesit (mm ²)	Anma Çapı (Ø)	Renk	Ağırlık (m)
Part No.	Material	Cross-Sectional Area (mm ²)	Nominal Diameter (Ø)	Colour Range	Weight (m)
ET.İCSY.SW.10	Cu	10	6.10 mm	S&Y/Green&Yellow	0,11
ET.İCSY.SW.16	Cu	16	6.80 mm	S&Y/Green&Yellow	0,17
ET.İCSY.SW.25	Cu	25	8.80 mm	S&Y/Green&Yellow	0,26
ET.İCSY.SW.35	Cu	35	9.80 mm	S&Y/Green&Yellow	0,35
ET.İCSY.SW.50	Cu	50	11.50 mm	S&Y/Green&Yellow	0,50
ET.İCSY.SW.70	Cu	70	13.20 mm	S&Y/Green&Yellow	0,68
ET.İCSY.SW.95	Cu	95	15.00 mm	S&Y/Green&Yellow	0,93
ET.İCSY.SW.120	Cu	120	17.00 mm	S&Y/Green&Yellow	1,17
ET.İCSY.SW.150	Cu	150	19.00 mm	S&Y/Green&Yellow	1,45
ET.İCSY.SW.185	Cu	185	21.00 mm	S&Y/Green&Yellow	1,85
ET.İCSY.SW.240	Cu	240	24.50 mm	S&Y/Green&Yellow	2,35

Bakır iletkenler EN 60228 Class 2'ye göre üretilmektedir.

Copper conductors are manufactured according to EN 60228 Class 2

Cu: Bakır / Copper

Pvc Kaplı Örgülü Bakır İletkenler

Pvc Covered Stranded Copper Cable



Ürün Kodu	Malzeme	Kesit (mm ²)	Anma Çapı (Ø)	Renk	Ağırlık (m)
Part No.	Material	Cross-Sectional Area (mm ²)	Nominal Diameter (Ø)	Colour Range	Weight (m)
ET.İCS.SW.10	Cu	10	6.10 mm	Siyah/Black	0,11
ET.İCS.SW.16	Cu	16	6.80 mm	Siyah/Black	0,17
ET.İCS.SW.25	Cu	25	8.80 mm	Siyah/Black	0,26
ET.İCS.SW.35	Cu	35	9.80 mm	Siyah/Black	0,35
ET.İCS.SW.50	Cu	50	11.50 mm	Siyah/Black	0,50
ET.İCS.SW.70	Cu	70	13.20 mm	Siyah/Black	0,68
ET.İCS.SW.95	Cu	95	15.00 mm	Siyah/Black	0,93
ET.İCS.SW.120	Cu	120	17.00 mm	Siyah/Black	1,17
ET.İCS.SW.150	Cu	150	19.00 mm	Siyah/Black	1,45
ET.İCS.SW.185	Cu	185	21.00 mm	Siyah/Black	1,85
ET.İCS.SW.240	Cu	240	24.50 mm	Siyah/Black	2,35

Bakır iletkenler EN 60228 Class 2'ye göre üretilmektedir.

Copper conductors are manufactured according to EN 60228 Class 2

Cu: Bakır / Copper